


Size	ØNB	L	ØD	Øf	B	'C'	ØG	H
1"	25mm	203	125	51	17	88.9	19.05	4
1½"	40mm	229	155	73	21	114.3	22.09	4
2"	50mm	267	165	92	22.3	127	19.05	8
2½"	65mm	292	190	105	25.4	149.2	22.09	8
3"	80mm	318	210	127	29	168.3	22.3	8
4"	100mm	356	255	157	31.75	200	22.3	8
5"	125mm	400	280	185.6	35	235	22.3	8
6"	150mm	444	320	216	36.5	269.9	22.3	12
8"	200mm	559	380	269.7	41.1	330.2	25.4	12
10"	250mm	622	445	323.8	47.7	387.4	28.5	16

SR. NO.	PARTS NAME	MATERIAL
1	BODY	ASTM A 216 Gr. WCB
2	COVER	ASTM A 216 Gr. WCB
3	SCREEN	SS 304
4	GASKET	SS 304 SPIRAL WOUND WITH GRAPHOL FILLER
5	BOLT & NUT	ASTM A 193 Gr. B7 / A193 Gr. 2H

TECHNICAL DATA	
DESIGN & MANUFACTURING STD.:	ASME B16.34
END CONNECTIONS :	FLANGED AS PER ASME B 16.5 - 150#

HYD. TEST PRESSURE	
BODY	
	79 KG/CM2

DRN. : B.M.P	 <p>NORFLOW CONTROLS Industrial Valves</p>
CHK.: V.G.P	
APRD.: S.K.P	
DATE:01.04.19	
SCALE.: NTS	Y STRAINER FLANGED ENDS
DRG NO. : NC/STR/DP/300/25 - 250	