


Size	ØNB	L	ØD	Øf	B	'C'	ØG	H
1"	25mm	216	125	51	17	88.9	19.05	4
1½"	40mm	241	155	73	22	114.3	22.09	4
2"	50mm	292	165	92	25.4	127	19.05	8
2½"	65mm	330	190	105	29	149.2	22.09	8
3"	80mm	356	210	127	31.7	168.3	22.3	8
4"	100mm	432	275	157	38.1	215.9	25.4	8
5"	125mm	508	330	185.6	44.4	266.7	28.4	8
6"	150mm	559	355	216	47.7	292.1	28.4	12
8"	200mm	660	420	269.7	55.6	349.2	31.75	12
10"	250mm	787	510	323.8	63.5	431.8	35.05	16

SR. NO.	PARTS NAME	MATERIAL
1	BODY	ASTM A 216 Gr: WCB
2	COVER	ASTM A 216 Gr: WCB
3	SCREEN	SS 304
4	GASKET	SS 304 SPIRAL WOUND WITH GRAPHOLIL FILLER
5	BOLT & NUT	ASTM A 193 Gr: B7 / A193 Gr: 2H

TECHNICAL DATA	
DESIGN & MANUFACTURING STD.:	ASME B16.34
END CONNECTIONS :	FLANGED AS PER ASME B 16.5 - 150#

HYD. TEST PRESSURE	
BODY	156 KG/CM2

DRN. : B.M.P	
CHK.: V.G.P	
APRD.: S.K.P	
DATE:01.04.19	
SCALE: NTS	Y STRAINER FLANGED ENDS
DRG NO. : NC/STR/DP/600/25-250	